



Notes

- 1. All Dims in mm Unless Otherwise Stated
- 2. Do Not Scale From This Drawing
- 3. Isolate All Dissimilar Materials With Barrier Tape
- 4. If in Doubt, ASK

NOTES:  
ALUMINIUM RIDGE FLASHING RIVETTED TO SLIDING RIDGE CLIP IN TWO PLACES WITH Ø4.8 mm x APPROX. 12 mm LONG ALUMINIUM BLIND SEALED TYPE RIVETS (WITH STAINLESS STEEL MANDREL), OR Ø5 mm x APPROX. 20 mm LONG ALUMINIUM 'BULB-TITE' TYPE NEOPRENE SEALED RIVETS (WITH ALUMINIUM MANDREL).  
RIVET TYPE TO BE DETERMINED BY GAUGE, LENGTH AND SHAPE OF FLASHING



This drawing is copyright and is issued on the express condition that it is not to be copied or disclosed by or to any unauthorised person or firms without prior consent in writing from Kalzip.



A Tata Steel Enterprise

Kalzip Ltd

Haydock Lane, Haydock, St. Helens  
MERSEYSIDE, WA11 9TY

Tel: 01942 295 500

Fax: 01942 295 508

Project:

Double Skin Constructions

Client:

Kalzip Ltd.

Title:

Double Skin Sliding  
Ridge Detail

Scale:	Date:	Drawn:	Checked:
1:5	19/07/05	KRT	

Dwg No.	Rev:
KAL-0-DS-L-2-003	F