



System Specification



ROOF LIGHT FIXED THROUGH CRESTS INTO SUPPORT BAR.

|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|  |  |  |  |

| PERFORMANCE                             |     |       |  |
|---|-----|-------|--|
| UV-Value Triple Skin (14-20% Roof Area) | TBC | W/m²K |  |
| UV-Value Double Skin (<14% Roof Area)   | TBC | W/m²K |  |
| F - Factor (Triple Skin)                |     | TBC   |  |
| F - Factor (Double Skin)                |     | TBC   |  |
| Humidity Classes                        |     | TBC   |  |



**Kalzip Ltd**  
Haydock Lane, Haydock, St. Helens  
MERSEYSIDE, WA11 9TY  
Tel: 01942 717072  
Fax: 01942 715713

This drawing is copyright and is issued on the express condition that it is not to be copied or disclosed by or to any unauthorised person or firms without prior consent in writing from Kalzip Ltd.

|  |                |           |          |
|--|----------------|-----------|----------|
| Title: Kal-Lite Site Assembled GRP RL800 Rooflight. Foot Detail #5/6 |                |           |          |
| Scale: NTS   | Date: 01/10/02 | Drawn: JW | Checked: |
| Dwg No. KLGRP800-A-04  |                | Rev: A    |          |